

DEUTZ POWERED DIESEL GENERATORS

30 TO 550 KVA - 3 PHASE - 415 VOLT - 1500 RPM

MODEL	STANDBY RATING			PRIME RATING			ENGINE BRAND		DIMENSIONS	WEIGHT	FUEL TANK SIZE	FUEL CONSUMPTION		NOISE LEVEL	ENGINE INTERVALS
	KVA	KW	AMPS (0.8 pf)	KVA	KW	AMPS @ .8 pf	ENG MODEL	GOV	L x W x H in mm	EST KG.	LTR/ HRS @ 75% LOAD	gr/kWh	ST/BY LTRS P/HR	7 METERS F.F.L.	CHECK O&M MANUAL
GP 30A/D	30	24	42	27	22	38	F4M 1011 (OIL COOLED)	Mech	1750 X 700 X 1100	710	215ltrs/45hrs	214	6	NA	1000hrs
GP 30S/D(120ltrs)									2100 X 900 X 1170	984	120ltrs/25hrs			65	1000hrs
GP 30S/D(430ltrs)									2100 X 900 X 1170	984	430ltrs/91hrs			65	1000hrs
GP 44A/D	44	35	61	40	32	56	BF4M 1011 (OIL COOLED)	Mech	1750 X 700 X 1100	820	245ltrs/36hrs	212	9	NA	1000hrs
GP 44S/D(120ltrs)									2100 X 900 X 1170	1030	120ltrs/18hrs			65	1000hrs
GP 44S/D(430ltrs)									2100 X 900 X 1170	1030	430ltrs/64hrs			65	1000hrs
GP 66A/D	66	53	92	60	48	83	BF4M 2012	Mech	2100 X 900 X 1300	1030	470ltrs/47hrs	219	14	NA	500hrs
GP 66S/D									2500 X 1000 X 1400	1340	490ltrs/49hrs			65	500hrs
GP 81A/D	81	65	113	76	61	106	BF4M 2012C	Mech	2100 X 900 X 1300	1100	560ltrs/45hrs	210	17	NA	500hrs
GP 81S/D									2500 X 1000 X 1400	1370	625ltrs/50hrs			70	500hrs
GP 115A/D	115	92	160	105	84	146	BF4M 1013EC	Mech	2100 X 900 X 1300	1170	24Hrs	210	24	NA	500hrs
GP 115S/D									2850 X 1000 X 1400	1660	24Hrs			70	500hrs
GP 143A/D	143	114	199	130	104	181	BF4M 1013FC	Mech	2850 X 1000 X 1400	1400	24Hrs	215	28.3	NA	500hrs
GP 143S/D									3000 X 1100 X 1510	1700	850ltrs/40hrs			67	500hrs
GP 165A/D	165	132	230	150	120	209	BF6M 1013EC	Mech	2850 X 1000 X 1400	1640	24Hrs	201	32	NA	500hrs
GP 165S/D									3300 X 1100 X 1500	2000	1090ltrs/46hrs			70	500hrs
GP 198A/D	198	158	275	180	144	250	BF6M 1013ECG2	Electronic	2850 X 1000 X 1400	1800	24Hrs	223	41	NA	500hrs
GP 198S/D									3300 X 1100 X 1500	2100	1090ltrs/46hrs			73	500hrs
GP 220A/D	220	176	306	200	160	278	BF6M 1013FCG3	Electronic	3200 X 1300 X 1500	2000	24Hrs	226	45	NA	500hrs
GP 220SK/D									3300 X 1100 X 1500	2150	1090ltrs/33hrs			73	500hrs
GP 220S/D									4000 X 1250 X 2200	2750	1400ltrs/42 hrs			70	500hrs
GP 275A/D	275	220	383	250	200	348	TCD2013L06-4V	Electronic	3200 X 1300 X 1500	2600	24Hrs	198	53	NA	500hrs
GP 275S/D									4000 X 1250 X 2200	3500	1400ltrs/35 hrs			70	500hrs
GP 330A/D	330	264	459	300	240	417	BF6M 1015C-G2	Electronic	3200 X 1300 X 2300	2900	24Hrs	198	63.8	NA	500hrs
GP 330S/D									4500 X 1450 X 2300	3900	2000ltrs/42Hrs			70	500hrs
GP 385A/D	385	308	536	350	280	487	BF6M 1015C-G3	Electronic	3200 X 1300 X 2300	3200	24Hrs	198	74.3	NA	500hrs
GP 385S/D									4500 X 1450 X 2300	4250	2000ltrs/36Hrs			70	500hrs
GP 440A/D	440	352	612	400	320	556	BF8M 1015C-G1	Electronic	3200 X 1300 X 2200	3800	24Hrs	198	85	NA	500hrs
GP 440S/D									5000 X 1900 X 2400	5000	2000ltrs/31Hrs			70	500hrs
GP 480A/D	480	384	668	450	360	626	BF8M 1015C-G2	Electronic	3200 X 1300 X 2200	4000	24Hrs	198	92	NA	500hrs
GP 480S/D									5000 X 1900 X 2400	5200	2800ltrs/40hrs			70	500hrs
GP 550A/D	550	440	765	500	400	696	BF8M 1015CP	Electronic	3200 X 1300 X 2200	4200	24Hrs	195	106	NA	500hrs
GP 550S/D									5000 X 1900 X 2400	5400	2800ltrs/35hrs			70	500hrs