

PERKINS POWERED DIESEL GENERATORS

30 TO 700 KVA - 3 PHASE - 415 VOLT - 1500 RPM

MODEL	STANDBY RATING			PRIME RATING			ENGINE BRAND		DIMENSIONS	WEIGHT	FUEL TANK SIZE	FUEL CONSUMPTION		NOISE LEVEL
	KVA	KW	AMPS (.8 pf)	KVA	KW	AMPS (.8 pf)	ENG MODEL	GOV	L x W x H in mm	KG.	LTR/ HRS @ 75% LOAD	gr/kWh	ST/BY LTRS P/Hr	7 METERS F.F.L.
GP 33A/P	33	26	46	30	24	42	1103A-33G	Mech	1750 X 700 X 1100	710	24Hrs	214	7.9	NA
GP 33S/P									2100 X 900 X 1170	984	24Hrs			67
GP 44A/P	44	35	61	40	32	56	1103A-33TG1	Mech	1750 X 700 X 1100	850	24Hrs	221	12	NA
GP 44S/P									2100 X 900 X 1170	1100	24Hrs			65
GP 66A/P	66	53	92	60	48	83	1103A-33TG2	Mech	2100 X 900 X 1300	920	24Hrs	267	17	NA
GP 66S/P									2500 X 1000 X 1400	1370	24Hrs			65
GP 88A/P	81	70	122	80	64	111	1104A-44TG2	Mech	2100 X 900 X 1300	1150	24Hrs	262	22	NA
GP 88S/P									2500 X 1000 X 1400	1470	24Hrs			70
GP 110A/P	110	88	153	100	80	139	1104C-44TAG2	Electronic	2850 X 1000 X 1400	1480	24Hrs	232	25	NA
GP 110S/P									3000 X 1100 X 1500	1950	24Hrs			70
GP 143A/P	143	110	191	130	104	181	1006TAG	Electronic	2850 X 1000 X 1400	1480	24Hrs	237	32	NA
GP 143S/P									3000 X 1100 X 1510	950	24Hrs			70
GP 165A/P	165	132	230	150	120	209	1006TAG2	Electronic	2850 X 1000 X 1400	1640	24Hrs	280	45	NA
GP 165S/P									3300 X 1100 X 1500	2200	24Hrs			70
GP 220A/P	220	176	306	200	160	278	1306-E87TAG3	Electronic	3000 X 1100 X 1500	1650	24Hrs	206	47	NA
GP 220SK/P									4000 X 1250 X 2200	2800	24Hrs			70
GP 220S/P									4000 X 1250 X 2200	2800	24Hrs			70
GP 275A/P	275	220	383	250	200	348	1306-E87TAG6	Electronic	3200 X 1300 X 1500	2600	24Hrs	206	56	NA
GP 275S/P									4000 X 1250 X 2200	3500	24Hrs			70
GP 385A/P	385	308	536	350	280	487	2306C-E14TAG2	Electronic	3200 X 1300 X 2300	3200	24Hrs	197	74	NA
GP 385S/P									4500 X 1450 X 2300	4250	24Hrs			70
GP 440A/P	440	352	612	400	320	556	2306C-E14TAG3	Electronic	3200 X 1300 X 2200	3800	24Hrs	199	88	NA
GP 440S/P									4500 X 1450 X 2300	4600	24Hrs			70
GP 495A/P	495	396	689	450	360	626	2506C-E15TAG1	Electronic	3200 X 1300 X 2200	4000	24Hrs	206	106	NA
GP 495S/P									5000 X 1900 X 2400	4700	24Hrs			70
GP 550A/P	550	440	765	500	400	696	2506C-E15TAG2	Electronic	3200 X 1300 X 2200	3600	24Hrs	205	114	NA
GP 550S/P									5000 X 1900 X 2400	4800	24Hrs			70
GP 605A/P	605	484	842	550	440	765	2506C-E18TAG1	Electronic	3400 X 1400 X 2200	4000	24Hrs	199	128	NA
GP 605S/P									5000 X 1900 X 2400	5200	24Hrs			70
GP 700A/P	700	560	974	650	520	904	2506C-E18TAG2	Electronic	3500 X 1600 X 2100	4100	12Hrs	202	141	NA
GP 700S/P									5500 X 1900 X 2400	5300	12Hrs			70